

nines

SERIES: MOSQUITO, TIGER, SHARK & DRAGON



Orientable Head V-H, 4x90°



**TAP UP TO
M27 1"**

(90kg./mm2)
M30 (aluminium)



Model R-TIGER



Reach 1020 mm. -40"
Height 535 mm. -21"

- TAP UP TO M27 – 1"
- 220/230 V. Single Phase
- High frequency motor
- Speed control forward & reverse
- 1 Motor 7 speed capabilities
- 7 interchangeable speed modules
- Heavy duty cast aluminium construction

OPTIONS AVAILABLE

- Vertical tapping
- Vertical & Horizontal tapping -VH- {4x90°}
- Tool lubrication with timer
- Tapping depth control

Description	Head Orientation	Speed RPM	Capacity (Steel 90 kg./mm ²)	
			Metric	Inch
ROSCAMAT TIGER	Vertical	90 -1050	M2-M27	#0 – 1"
ROSCAMAT TIGER VH	Vertical & Horizontal	90 -1050	M2-M27	#0 – 1"

Modular System - Interchangeable Speed

Module	Max. speed. (rpm)	Torque max.		Adapter Size	Tapping Capacity - Steel <90kg	
		Nm	Ft•lb		Metric	Inches
90	90	150	66	ø 31	M16-M27	1/2" – 1"
170	170	79	58	ø 31	M16-M20	1/2" – 3/4"
300	300	44	32	ø 19	M2- M16	#0 – 9/16"
550	550	24	15	ø 19	M2-M12	#0 – 1/2"
750	750	17	13	ø 19	M2-M10	#0 – 3/4"
1050	1050	12,5	9	ø 19	M2-M8	#0 – 5/16"
2100	2100	6	4	B-16 cone	Drills up to ø8 aluminium, Cast Iron, etc	



Modules for Model R-TIGER & R-DRAGON